



RW 16 basic

Electronically controlled laboratory stirrer for stirring tasks up to 10 liters.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	40 – 1.200 rpm
Motor rating input/output	75/55 W
Max. viscosity	10.000 mPa·s
Max. torque at chuck	40 Ncm



Ident. No. 2572100

687,00 €

T 18 basic ULTRA-TURRAX® Package

Dispersing unit for volumes from 10 to 1.500 ml.
Package includes T 18 basic + dispersing element S 18 N - 19 G.

Technical data	
Volume range (H ₂ O)	10 – 1.500 ml
Speed range	3.500 – 24.000 rpm
Motor rating input/output	500/300 W
Max. viscosity	5.000 mPa·s
Speed display	scale



Package without stand and clamps

Ident. No. 9018900

740,00 €

topolino IKAMAG®

Extremely convenient mini-stirrer for quantities up to 250 ml.

Technical data	
Stirring quantity (H ₂ O)	250 ml
Speed range	30 – 1.800 rpm
Motor rating input/output	1,1/0,8 W



Ident. No. 3368000

74,00 €

RH basic 2 IKAMAG®

Magnetic stirrer with stainless steel heating plate.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	100 – 2.000 rpm
Temperature range	RT – 320 °C
Heat output	400 W
Speed-/Temperature display	scale (0 – 6)



Ident. No. 3339000

274,00 €

C-MAG HS 7 IKAMAG®

Magnetic stirrer with ceramic heating plate. Bushing according to DIN 12878 for connecting a contact thermometer, e.g. ETS-D5.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	100 – 1.500 rpm
Temperature range	50 – 500 °C
Heat output	1.000 W
Speed-/Temperature display	scale/digital



Ident. No. 3581200

369,00 €

C-MAG HS 7 IKAMAG® Package

Package includes C-MAG HS 7, contact thermometer ETS-D5, support rod H 16 V, holding rod H 38 and boss head clamp H 44.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	100 – 1.500 rpm
Temperature range	50 – 500 °C
Heat output	1.000 W
Speed-/Temperature display	scale/digital



Ident. No. 9015900

475,00 €



C-MAG HS 7 IKAMAG® Package

475,00 €

Please contact your local dealer or

IKA®-Werke GmbH & Co. KG
Janke & Kunkel-Str. 10
79219 Staufen · Germany
Tel.: +49 7633 831-0 · Fax: +49 7633 831-98
E-Mail: sales@ika.de · www.ika.net



Designed to work perfectly



Designed to work perfectly

201101_Best_Value_EN_EUR

KS 130 & KS 260 Packages – unshakable performance from IKA®



KS 130 basic Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 2 kg. LED display for speed and time.

Technical data	
Shaking motion	orbital
Speed range	80 – 800 rpm
Orbital diameter	4 mm
Max. shaking weight	2 kg
Timer	5 – 50 min

Ident. No. 9019000

740,00 €



STICKMAX
Adhesive mat
Ident. No. 3920000

AS 130.3
Dish attachment
Ident. No. 3120000

KS 130 control Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 2 kg. Digital display for speed and time. Integrated end point positioning and interface RS 232 to control and document automatic processes.

Technical data	
Shaking motion	orbital
Speed range	80 – 800 rpm
Orbital diameter	4 mm
Max. shaking weight	2 kg
Timer	0 – 9 h 59 min
Digital display	speed, time
Interface	RS 232

Ident. No. 9019100

1.044,00 €




STICKMAX
Adhesive mat
Ident. No. 3920000

AS 130.3
Dish attachment
Ident. No. 3120000

STICKMAX

New universal adhesive mat for the fixing clip attachments of KS 130, KS/HS 260, KS/HS 501 and KS 4000 shakers.

- Ideal for frequently changing vessel types and sizes
- Self-adhesive
- Vessels can be easily removed thanks to side fitting movement
- Suitable for disinfection
- Peel-away strength required: 5 N/cm²
- Dimensions (W x D): 200 x 200 mm



KS 260 basic Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 7,5 kg. LED display for speed and time adjustment.

Technical data	
Shaking motion	orbital
Speed range	20 – 500 rpm
Orbital diameter	10 mm
Max. shaking weight	7,5 kg
Timer	5 – 50 min

Ident. No. 9019200

1.017,00 €



2x STICKMAX
Adhesive mat
Ident. No. 3920000

AS 260.3
Dish attachment
Ident. No. 3120600

KS 260 control Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 7,5 kg. Digital display for speed and time. Integrated end point positioning and interface RS 232 to control and document automatic processes.

Technical data	
Shaking motion	orbital
Speed range	10 – 500 rpm
Orbital diameter	10 mm
Max. shaking weight	7,5 kg
Timer	0 – 9 h 59 min
Digital display	speed, time
Interface	RS 232

Ident. No. 9019300

1.323,00 €



2x STICKMAX
Adhesive mat
Ident. No. 3920000

AS 260.3
Dish attachment
Ident. No. 3120600

Shakers accessories (KS 130 / KS 260)

AS 130.1 Universal attachment
Ident. No. 8017300 **148,00 €**




AS 130.2 Fixing clip attachment
Ident. No. 3115000 **62,50 €**



AS 130.4 Test tube support
Ident. No. 3120300 **148,00 €**



AS 260.1 Universal attachment
Ident. No. 8017400 **180,00 €**



AS 260.2 Fixing clip attachment
Ident. No. 3115500 **94,00 €**



AS 2.1 Fixing clip, 25 ml
Ident. No. 1234300 **15,90 €**



AS 2.2 Fixing clip, 50 ml
Ident. No. 1234400 **15,90 €**



AS 2.3 Fixing clip, 100 ml
Ident. No. 1234500 **15,90 €**



AS 2.4 Fixing clip, 200/250 ml
Ident. No. 1234600 **31,50 €**



AS 2.5 Fixing clip, 500 ml
Ident. No. 1234700 **31,50 €**



AS 2.6 Fixing clip, 1000 ml
Ident. No. 3819300 **31,50 €**

