

Beer Bottle Shaker SM 30 B control



Description

The laboratory shaker SM 30 B control with a horizontal shaking motion up to 240 rpm and a stroke of 50 mm is ideally suited for Gushing Tests. It also has a digital display with programmable control. Up to 6 horizontal bottles (0,33 l or 0,5 l) can be fixed on the shaker with the suitable rack system. With a loading capacity of max. 30 kg it can be supplied with a two- or three-storey top frame.

Basic Equipment

Basic device with shaking plate and rubber mat, **without rack system**

With digital display and programmable control

Loading Capacity

Up to 6 horizontal bottles (0,33 or 0,5l) per storey

1-storey, 2-storey or 3-storey rack system can be selected as accessories

[Loading details](#) against shaking speed

Option:[Control interface](#)[USB interface](#)

Details

Motion:	reciprocating (horizontal)
Shaking platform:	560 x 400 mm
Max. load:	30 kg
Shaking speed:	up to 240 rpm, in steps of 5
Stroke:	50 mm for Gushing Test (No. 0052 216)
Runtime:	programmable / continuous
Order No.:	6102 000
Accessory:	1-storey top frame 2-storey top frame 3-storey top frame

Technical specifications

Electrical supply:	230 V or 115 V, 50 / 60 Hz please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	approx. 20 - 30 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	680 x 610 x 160 mm
Weight:	33 kg