

Compact Shaker KS 15 A control



Description

The programmable Orbital Shaker KS 15 A control with digital display for reproducible shaking tasks. The loading capacity is 15 kg on a shaking platform of 400 x 300 mm.

Basic Equipment

Basic device without shaking plate, **without rack system**
With digital display and programmable control.

Loading Capacity

Erlenmeyer flasks 100 ml	20 pieces
Erlenmeyer flasks 250 ml	12 pieces
Erlenmeyer flasks 500 ml	6 pieces
Erlenmeyer flasks 1000 ml	4 pieces
Separating funnels 250 ml	1 pieces

You will find further loading possibilities [here](#)

Option:[Control interface](#)[USB interface](#)

Details

Motion:	orbital
Shaking platform:	400 x 300 mm
Max. load:	15 kg
Shaking speed:	30 - 420 rpm, in steps of 5
Stroke:	17 mm
Runtime:	programmable / continuous
Order No.:	6170 000
Accessory:	Rack System Combifix KS Universal tray KS Incubator Hood TH 15

Technical specifications

Electrical supply:	230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	approx. 10 - 15 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	510 x 490 x 150 mm
Weight:	19 kg