Miniature Shaker KM CO2



Description

The shaker KM CO_2 made of stainless steel with orbital shaking motion was especially designed for use in incubators with up to 20% CO_2 concentration and up to 95% humidity. This guarantees the optimum development of your cell cultures.

Basic Equipment
Basic device incl. basic platform with rubber mat and external control unit

Loading Capacity
Erlenmeyer flasks 100 ml 9 pieces
Erlenmeyer flasks 500 ml 2 pieces

You will find further loading possibilities here

Details

Motion:	orbital

Edmund Bühler GmbH,
Schindäckerstraße 8,
D-72411 Bodelshausen,
Tel: +49 (0) 74 71 / 98 64-0
info@edmund-buehler.de

Shaking platform:	200 x 295 mm
Max. load:	2 kg
Shaking speed:	5 - 220 rpm, in steps of 5
Stroke:	20 mm
Runtime:	1s - 100 h / continuous
Order No.:	6136 000
Accessory:	Universal tray KM Mini Universal tray KM Clamping strip KM

Technical specifications

Electrical supply:	100 - 240 V, 50 / 60 Hz
Enclosure protection:	IP 21
Heat emission:	approx. 4 W
Ambient temperature:	4°C to 45°C
Relative humidity:	20 - 95 %
CO2 concentration:	20 %
Dimensions (w x d x h):	230 x 340 x 145 mm
Weight:	7,6 kg

Edmund Bühler GmbH,
Schindäckerstraße 8,
D-72411 Bodelshausen,
Tel: +49 (0) 74 71 / 98 64-0
info@edmund-buehler.de